



# VIALE SISTEMI SRL

DVF2E

## GEAR MOTOR SERIE DVF2E

### GEAR MOTOR FOR TOP VENTILATION AND SHADING SYSTEM

Complete range from 350 to 450 Nm (inch/pound 2920-3720).

Limit switch in a separate aluminium case with double safety switch.

Electric motor with hex wrench for use in case of power failure. Options: motors three-phases and single-phase with capacitor run and capacitor start for high torque start.

Designed for top ventilation and shading systems.

Normal shaft direct in stainless steel or chain coupling.

Quality aluminium finishing – easy to install – compact design.

Motors with service type S1 (continuous service).

On demand special motors 50-60 Hz with UL CSA certifications.



Code	DVF2E-935		DVF2E-950		DVF2E-1450		DVF2E-141	
	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz
Frequency	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz	50 Hz	60 Hz
Kw	0,25	0,25	0,37	0,37	0,37	0,37	0,75	0,75
A a 400v	1	1	1,25	1,25	1,15	1,15	1,55	1,55
Protection level	IP55	IP55	IP55	IP55	IP55	IP55	IP55	IP55
RPM	2	2,3	2	2,3	2,7	3	2,7	3
Nm	350	330	420	400	350	330	450	420



**SISTEMA QUALITA' CERTIFICATO  
UNI EN ISO 9001 / 2008**

